

Zátěžová tabulka pro rovnoměrné zatížení v (kg)

POLICE	DĚLKA	600 mm		900 mm				1050mm				1200mm				1350mm			1500mm						1650mm			1800mm			
		HLOUBKA	TYP PANELU	S0	S1	S0	S1	S2	S3	S0	S1	S2	S3	S0	S1	S2	S3	S1	S2	S3	S1	S2	S3	S1G	S2G	S3G	S1	S2	S3	S3	S1G
320mm	H12	200	280	200	280	310	310	170	240	340	370	150	210	280	320	180	220	250	150	180	210	350	520	520	120	150	170	140	310	430	530
	VANOVÉ	180	180	200	270	270	270	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	450	450	-	-	-	140	310	430	530
	PLASTOVÉ	90	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	150	180	210	220	220	220	120	150	170	140	270	270	270
400mm	H12	200	240	200	240	240	240	170	240	280	280	150	210	280	320	180	220	250	150	180	210	350	400	400	120	150	170	140	310	430	470
	H25A	200	280	200	280	390	450	170	240	340	390	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25B	200	280	200	280	390	450	170	240	340	390	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25C - PERFOROVANÉ	200	280	200	280	390	450	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	520	640	-	-	-	140	310	430	530
	VANOVÉ	180	180	200	270	270	270	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	450	450	-	-	-	140	310	430	530
PLASTOVÉ	90	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	150	180	210	220	220	220	120	150	170	140	270	270	270	
500mm	H12	180	180	180	180	180	180	170	230	230	230	150	210	260	260	180	220	250	150	180	210	320	320	320	120	150	170	140	310	370	370
	H25A	200	280	200	280	390	420	170	240	340	370	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25B	200	280	200	280	390	450	170	240	340	390	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25C - PERFOROVANÉ	200	280	200	280	390	450	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	520	640	-	-	-	140	310	430	530
	VANOVÉ	140	140	200	210	210	210	-	-	-	-	150	210	280	280	-	-	-	150	180	210	350	350	350	-	-	-	140	310	420	420
PLASTOVÉ	90	90	135	135	135	135	150	150	150	150	150	180	180	180	180	200	200	150	180	210	220	220	220	120	150	170	140	270	270	270	
600mm	H12	150	150	150	150	150	150	170	180	180	180	150	210	210	210	180	220	230	150	180	210	260	260	260	120	150	170	140	310	310	310
	H25A	200	230	200	280	350	350	170	240	320	340	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25B	200	260	200	280	390	390	170	240	340	360	150	210	280	320	180	220	250	150	180	210	350	520	640	120	150	170	140	310	430	530
	H25C - PERFOROVANÉ	200	240	200	280	360	360	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	520	600	-	-	-	140	310	430	530
	VANOVÉ	130	130	200	200	200	200	-	-	-	-	150	210	260	260	-	-	-	150	180	210	330	330	330	-	-	-	140	310	390	390
PLASTOVÉ	60	60	90	90	90	90	110	110	110	110	120	120	120	120	140	140	140	150	150	150	150	150	150	120	150	170	140	180	180	180	
700mm	H12	130	130	130	130	130	130	150	150	150	150	150	180	180	180	180	200	200	150	180	210	220	220	220	120	150	170	140	260	260	260
	H25A	180	180	200	280	280	280	170	240	280	300	150	210	280	320	180	220	250	150	180	210	350	480	480	120	150	170	140	310	430	530
	H25B	200	220	200	280	330	330	170	240	310	320	150	210	280	320	180	220	250	150	180	210	350	520	550	120	150	170	140	310	430	530
	H25C - PERFOROVANÉ	190	190	200	280	280	280	-	-	-	-	150	210	280	320	-	-	-	150	180	210	350	480	480	-	-	-	140	310	430	530
	VANOVÉ	120	120	180	180	180	180	-	-	-	-	150	210	240	240	-	-	-	150	180	210	300	300	300	-	-	-	140	310	360	360
800mm	H25A	150	150	200	230	230	230	170	200	240	260	150	180	250	290	150	200	240	130	160	180	350	430	430	120	150	150	130	280	350	480
	H25B	180	180	200	250	260	260	170	220	250	280	150	180	250	290	150	200	240	130	160	180	350	480	480	120	150	150	130	280	350	480
	H25C - PERFOROVANÉ	140	140	210	210	210	210	-	-	-	-	150	210	280	280	-	-	-	150	180	210	350	350	350	-	-	-	140	310	420	420
	VANOVÉ	120	120	180	180	180	180	-	-	-	-	150	210	240	240	-	-	-	150	180	210	300	300	300	-	-	-	140	310	360	360
PNEU		-		180				-				120				-			130						-			-			

NOSNOST RÁMŮ

SUPER S0	SUPER S1	SUPER S2	SUPER S3	UNIRACK USA	UNIRACK USB
1100	1700	2000	3600	2600	3000